



ENDOEYE 3D 10 MM

Video Telescope



3D-Image Rotation without Loss of Horizon

· Change the view direction while maintaining horizontal orientation of images, enabling a continuous critical view in 3D

Chip-on-the-Tip Technology

- · Bright, clear, and natural 3D depth perception
- · Focus-free handling; no manual focusing required

Autoclave Compatibility

· Reduced costs compared with other sterilization methods

Full Control During Surgery

 \cdot Three programmable remote control buttons

Plug and Play

 \cdot Simple to set up and easy to use

Ordering Information									
Order Number	Outer Diameter	Direction of View	Field of View	Working Length	Max. Insertion Portion Width	Cable Length	Weight		
WA50080A	10 mm	0°	67°	330 mm	10.07 mm	2780 mm	290g		
WA50082A	10 mm	30°	67°	335 mm	10.20 mm	2780 mm	290g		

Specifications							
Reprocessing Methods	Autoclavable, ETO, STERRAD, washer-disinfector						
	Operating conditions	Ambient temperature	10 to 35°C (50 to 95°F)				
	Operating conditions	Relative humidity	30 to 85%				
Ambient	Storage conditions	Temperature	10 to 40°C (50 to 104°F)				
Conditions	Storage conditions	Relative humidity	30 to 75%				
	Transport conditions	Temperature	-47 to 70°C (-53 to 158°F)				
	nansport conditions	Relative humidity	10 to 95%				
Classification of ME Equipment - and ME Systems	Protection against electric shock: Classifi	cation of applied parts	Type BF				
	Protection against harmful ingress of wat	er or particulate matter	IPX7				