

## EVIS LUCERA E L I T E

EVIS LUCERA ELITE VIDEOCOLONOSCOPE

# PCF-H290TL/I

High-definition colonoscope facilitating endoscopic treatment through excellent maneuverability











#### **Main Features**

#### Short bending for better access to lesions

With a shorter bending section, the PCF-H290TL/I provides better handling in the intestine. Combined with the 210° up angulation, the scope offers easier lesion approachability.





PCF-H290TL/I

PCF-Q260JL/I

### **HDTV** and NBI


With its HDTV image quality and brighter NBI, the PCF-H290TL/I contributes to higher treatment accuracy. High confidence optical diagnosis facilitates appropriate treatment decisions and accurate delineation of lesions.



White Light

#### Appropriate channel layout

The layout allows for smooth operation of both the water-jet function and any treatment such as stopping bleeding.



#### Improved insertability

The PCF-H290TL/I incorporates unique proprietary OLYMPUS technologies, realizing easier scope insertion with minimized patient discomfort.



EVIS LUCERA ELITE Videocolonoscope OLYMPUS PCF-H290TL/I

Optical System	Field of view (Maximum diagonal angle) 140°		Instrument Channel	Direction from which EndoTherapy accessories enter and exit the	
	Direction of view 0°(Forward viewing)				
	Depth of field	5–100 mm		endoscopic image	
Insertion Section	Distal end outer diameter	9.8 mm		Direction of water jet in field of view	
	Distal end enlarged Objective Lens	Up Air/Water Nozzle	Water Jet		
	Right Q Left				Up 210°
	Instrument Channel	Light-guide Lens	Bending	A detien were	Down 180°
	Outlet Auxiliary Water Channel Down		Section	Angulation range	Right 160°
	Insertion tube outer diameter	10.5 mm			Left 160°
	Working length	L: 1680 mm, I: 1330 mm	Total Lengt	L: 2005 mm, I: 1655 mm	
Instrument Channel	Channel inner diameter	3.2 mm	Compatible EVIS	Video System Center OLYMPUS CV-290	
	Minimum visible distance	4 mm from the distal end	LUCERA System	Xenon Light Source OLYMPUS CLV-290SL,CLV-290	

Specifications, design, and accessories are subject to change without any notice or obligation on the part of the manufacturer.

