

Technical Specifications

Cyanide free	reagent for hemog	giodin test		
Performance	2			
Parameter	Linearity Range	Precision (CV %)	Carryover	
WBC(109/L)	0-100	≤3.5% (4.0-6.9)	≤0.5%	
		≤2.0% (7.0-15.0)		
RBC(10 ¹² /L)	0-8.00	≤1.5% (3.5-6.5)	≤0.5%	
HGB(g/L)	0-280	≤1.5% (100-180)	≤0.5%	
MCV(fL)		≤1.0% (70-110)		
PLT(10 ⁹ /L)	0-1000	≤5.0% (100-149)	≤1.0%	
		≤4.0% (150-500)		
Parameters				
	rs: WBC. Lymph#. N	/lid#. Gran#. Lymph	%. Mid%. Gran%. RBC.	
19 paramete	, , , , , , , , , , , , , , , , , , , ,		%, Mid%, Gran%, RBC, T. MPV, PDW, PCT	
19 paramete HGB, HCT, M	, , , , , , , , , , , , , , , , , , , ,	DW-CV, RDW-SD, PL		
19 paramete HGB, HCT, M	CV, MCH, MCHC, RI	DW-CV, RDW-SD, PL		
19 paramete HGB, HCT, M 3 histograms	CV, MCH, MCHC, RI	DW-CV, RDW-SD, PL		
19 paramete HGB, HCT, M 3 histograms Reagent	CV, MCH, MCHC, RI for WBC, RBC and	DW-CV, RDW-SD, PL		
19 paramete HGB, HCT, M 3 histograms Reagent M-30D DILUI	CV, MCH, MCHC, RI s for WBC, RBC and	DW-CV, RDW-SD, PL		
19 paramete HGB, HCT, M 3 histograms Reagent M-30D DILUI M-30CFL LYS	CV, MCH, MCHC, RI s for WBC, RBC and ENT	DW-CV, RDW-SD, PL		
19 paramete HGB, HCT, M 3 histograms Reagent M-30D DILUI M-30CFL LYS	CV, MCH, MCHC, RI s for WBC, RBC and ENT	DW-CV, RDW-SD, PL		
19 paramete HGB, HCT, M 3 histograms Reagent M-30D DILUI M-30CFL LYS PROBE CLEA	CV, MCH, MCHC, RI s for WBC, RBC and ENT SE NSER	DW-CV, RDW-SD, PL		
19 paramete HGB, HCT, M 3 histograms Reagent M-30D DILUI M-30CFL LYS PROBE CLEA Sample Volu	CV, MCH, MCHC, RI s for WBC, RBC and ENT SE NSER me	DW-CV, RDW-SD, PL PLT		
HGB, HCT, M	CV, MCH, MCHC, RI s for WBC, RBC and ENT SE NSER me 10de 20µL	DW-CV, RDW-SD, PL PLT		
19 paramete HGB, HCT, M 3 histograms Reagent M-30D DILUI M-30CFL LYS PROBE CLEA Sample Volu Prediluted m Whole blooc	CV, MCH, MCHC, RI s for WBC, RBC and ENT SE NSER me 10de 20µL	DW-CV, RDW-SD, PL PLT		
19 paramete HGB, HCT, M 3 histograms Reagent M-30D DILUI M-30CFL LYS PROBE CLEA Sample Volu Prediluted m	CV, MCH, MCHC, RI s for WBC, RBC and ENT SE NSER me tode 20μL I mode 9 μL	DW-CV, RDW-SD, PL PLT		

WIFI capability provides you an added option for data communication together with bi-directional LIS, USB port and LAN port, barcode reader, printer and keyboard.

www.mindray.com

P/N: ENG-BC-20s-210285x6-20170930 ©2017 Shenzhen Mindray Bio-Medical Electronics Co.,Ltd. All rights reserved.

mindray

Multi-language Chinese, English, Spanish, Portuguese, Russian, French, Bahasa Indonesia

Data Storage Capacity Up to 200,000 results including numeric and graphical information

Communication LAN Port supports HL7 protocol Support bi-directional LIS

Interface 4 USB port (for external printer, software upgrade, barcode reader, WIFI adapter,keyboard and mouse), LAN port (1)

Printout Thermal recorder, 50 mm wide paper, various printouts formats External printer optional

Operating EnvironmentTemperature:10°C~40°CHumidity:10%~90%Air pressure:70kPa~106kPa

Power Requirement 100V-240V ≤300VA 50Hz/60Hz

Dimension and Weight Dimension: Depth(410 mm) x width(300 mm) x height(400 mm) Weight: ≤20Kg



BC-20s Auto Hematology Analyzer

Minimum Size, Maximum Capability





BC-20s Auto Hematology Analyzer

Sample 1 : BC-20s shows flag "Lymph increased" which means a high number of Lymphocytes and/or immature cells. Meanwhile R1 flag is also displayed. Two kinds of flag messages are both supported to ensure clinicians have better understanding of sample results.

Sample 2 : Flag "Anemia" and "HGB Abn./Interfere?" are displayed. They mean the sample has shows either signs of Anemia, Abnormal Hemoglobin or sample is interfered such as by high value of Leukocytes or Agglutinated Erythrocytes.

Sample 3 : Flag "Thrombopenia" indicator is shown together with Platelets low flag.

Different flag information provided according to parameter results together with histograms.

What a 3-part should be

At Mindray we pride ourselves in our dedication and experience in developing better solutions for small labs. Our new line of 3-part hematology analyzers is the culmination of that effort. Compact yet powerful, full featured yet affordable, the BC-20s is what a 3-part analyzer should be.



Exclusive Feature

Detailed flag information never before seen on a 3-part analyzer. Provides information useful for diagnosis including WBC flag, RBC flag and PLT flag.





Better Usability

Minimum size with the footprint similar to that of a 17 inch laptop, with space saving design that allows internal storage of lyse giving small labs more space. 8.4 inch TFT touch screen together with our powerful software enhances user operations and experience.

Higher Efficiency

New technology that eliminates the need for cleanser and rinse, reducing the number of reagents needed while at the same time lowering overall reagent consumption.

Flexible packaging of reagents, with normal and small sizes to better cater to the needs of different daily sample volumes.









Enhanced Performance

Higher throughput at 40 tests per hour.

Micro sample volume at 9.0uL for whole blood mode with capillary whole blood samples supported, perfect for pediatric samples.